

7

DATA SHEET



www.hydron-pumps.com

ES-8-2



A range of cast aluminium evaporator trays with builtin electric elements for use with air conditioning, refrigeration and display case applications where the use of forced evaporation is required for condensate removal.

3 models offer evaporation rates of between 241 ml/hr and 454 ml/hr.

All three models come with mounting springs to prevent minimal heat transfer.

Models ES-8-2 & ES-16-12 are self regulating. An optional Kluxen thermal switch is available on request.

Model ES-8-2-T comes with built-in thermal regulators as well as thermal overload protection.

ES-16-2



ES-8-2-T



TECHNICAL SPECIFICATION

	ES-8-2	ES-16-12	ES-8-2-T
ELECTRICAL			
Voltage	230v 50Hz	230v 50Hz	230v 50Hz
Power	160 Watts	320 Watts	160 Watts
PERFORMANCE			
Evaporation Rate	241 ml/hr	454 ml/hr	241 ml/hr
Tank Capacity	1 litre	2 litres	1 litre
PHYSICAL			
Height	73mm	79 mm	79 mm
Length	111mm	229 mm	229 mm
Width	295mm	295 mm	295 mm

SANDYCOTT Ltd

Church Street, Eckington
 Sheffield, S21 4BH, England
 Phone: +44 (0) 1246 436632
 Fax: +44 (0) 1246 433372
 email: sales@hydron-pumps.com
 web: www.hydron-pumps.com

EVAPORATOR TRAYS